

**« Le Wing » Speakers : Technical Characteristics****POWER**

<b>Continuous power</b>	:	<b>80 W</b>
<b>Repetitive peak power</b>	:	<b>160 W</b>

**SPECIFICATIONS**

<b>Cabinet system</b>	:	<b>sealed</b>
<b>Number of ways</b>	:	<b>2</b>
<b>Midrange / Woofer</b>	:	<b>2 x T12PE80b</b>
<b>Diameter</b>	:	<b>120mm / 4.7"</b>
<b>Cone material</b>	:	<b>Cellulose pulp</b>
<b>Tweeter</b>	:	<b>TZ2400b</b>
<b>Diameter</b>	:	<b>25mm / 1"</b>
<b>Dome material</b>	:	<b>Titane</b>
<b>Number of speakers (L, C, R)</b>	:	<b>3</b>
<b>Number of drivers per speaker</b>	:	<b>3 (2 Mid/Woofer-1TW)</b>
<b>Frequency response (+/- 3dB)</b>	:	<b>100Hz – 20kHz</b>
<b>Sensitivity (dB/W/m)</b>	:	<b>90</b>
<b>Nominal impedance</b>	:	<b>8 ohms</b>
<b>Minimal impedance</b>	:	<b>4 ohms</b>
<b>High frequency roll-off</b>	:	<b>2 000 Hz (24dB/octave)</b>
<b>Recommended lower frequency cut</b>	:	<b>100 Hz (12dB/octave)</b>
<b>Terminal</b>	:	<b>single wire</b>
<b>Integrated electronic protection device</b>	:	<b>YES</b>
<b>Anti magnetic properties</b>	:	<b>YES</b>